



SR-32NE-I2



Key Features

- Support Ultra H.265/H.265/H.264 video formats
- 32-channel input
- Supports mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols
- HDMI & VGA independent outputs provided
- Up to 12 Megapixels resolution recording
- 2 SATA HDDs, up to 8TB for each HDD
- Various fisheye dewarping modes for live view & playback for both web interface & GUI
- ANR technology to enhance the storage reliability when the network is disconnected
- Support cloud upgrade



Specifications

SR-32NE-I2	
Video/Audio Input	
IP Video Input	32-Channel
Two-Way Audio	1-Channel, RCA
Network	
Incoming Bandwidth	320 Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS
Browser	IE (IE 10/11) for Windows Firefox (Version 52.0 & above) for Windows Chrome (Version 45 & above) for Windows Edge (Version 79 & above) for Windows
Video/Audio Output	
HDMI/VGA Output	VGA: 1920 x 1080p/60Hz, 1920 x 1080p/50Hz, 1600 x 1200/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz HDMI: 4K(3840 x 2160)/30Hz, 1920 x 1080p/60Hz, 1920 x 1080p/50Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz
Recording Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 960p, 720p, D1, 2CIF, CIF
Audio Output	1-Channel, RCA
Audio Compression	G.711A, G.711U
Synchronous Playback	16-Channel
Liveview Display	1, 4, 6, 8, 9, 16, 25, 36
Corridor Mode Screen	3, 4, 5, 7, 9, 10, 12, 16, 32
Snapshot	
FTP, Schedule, Event Snapshot	16-Channel snapshot, up to 1080p resolution
Decoding	
Decoding Format	Ultra 265, H.265, H.264
Liveview/Playback	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 960p, 720p, D1, 2CIF, CIF



Capability	1 x 12MP@30, 2 x 4K@30, 5 x 4MP@30, 10 x 1080p@30, 22 x 720p@30, 32 x D1
Hard Disk	
SATA	2 SATA interface
Capacity	Up to 8TB for each HDD (The max. HDD capacity varies with environment temp.)
eSATA	N/A
Disk Group	Support
Smart	
VCA Detection by Camera	Intrusion Detection, Cross Line Detection, Enter & Leave Area, Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed & Auto Tracking
VCA Search	Behavior Search & Vehicle Search
People Counting	People flow counting, crowd density monitoring
Smart Intrusion Prevention (SIP) by Camera	Total 8-Channel
General Alarm	
General Alarm	Motion, tampering, human body detection, video loss, alarm input & audio detection
Alert Alarm	IP Conflict, network disconnected, Disk offline, disk abnormal, illegal access, hard disk space low, hard disk full & recording/snapshot abnormal
External Interface	
Network Interface	2 RJ45 10M/100M/1000M Self-adaptive Ethernet interfaces
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0
RS232	N/A
RS485	1
Alarm In	8-Channel
Alarm Out	2-Channel
General	
Power Supply	12VDC/3.3A Power Consumption: ≤ 12 W (without HDD)
Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions	380mm × 315mm × 53mm (15.0" × 12.4" × 2.1") (W X D X H)



Weight (without HDD)	≤1.8Kg (3.97lb)
----------------------	-----------------

Certification

Certification	CE, FCC, UL, RoHS, WEEE
CE	EN 55032: 2015, EN 61000-3-3: 2013, EN IEC 61000-3-2: 2019, EN 55035: 2017
FCC	Part15 Subpart B, ANSI C63.4

Dimensions

