



NKB1000-E



Key Features



Keyboard to Control

- High Speed Dome
- Standalone DVR
- Network Video Server

Connection

- RS485, RS422 (reserved), USB, RS232 and Network Functions
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour and Pattern Auxiliary Functions
- On-Screen Menu and User Operation Procedure Tips
- Connect to SmartPSS or DSS platform via USB



Specifications

General		NKB1000-E	
Keyboard Key Panel	Electromechanical		
Joystick	3-Axis, vector-solving with twisting, return to-center head		
Keyboard Connector	RJ-45, RS232, RS485, RS422 (reserved), USB		
Keyboard Communication	Direct Mode, Network Mode		
Direct Mode	Interface: 1 RS232, 2 RS485 DVR Protocol: DH-2 Dome Protocol: DH-SD1, Pelco-D, Pelco-P, etc.		
Network Mode	Interface: RJ45 DVR, Network Dome: IP Address, Port, Protocol		
Display	LCD, 75.2mm x 33.85mm		
Max. Number of Users	64 (including “admin”)		
Max. RS485 Addresses (Each User)	256		
Max. Number of PTZ (IPC) That Can Be Added Over Network (Each User)	2048		
Environmental			
Power Supply	Power adapter Input: 100V ~ 240V 50Hz, 60Hz Output: DC12V/2A		
Power Consumption	5W		
Working Temperature	-10°C ~ +55°C		
Working Humidity	10% ~ 90%		
Atmosphere Pressure	86 kpa ~ 106 kpa		
Dimensions	330mm × 139mm × 53mm (W×D×H) (Height: 103mm including joystick)		
Weight	1.3kg (Including package)		



Dimensions

